

SPECIFICATION : ท่อ UPVC มาตรฐาน Sch.80

Nominal Size		Outside Diameter		Wall Thickness, Working Pressure (PSI @ 73°F) & Weight (lb/ft)			
				PVC SCHEDULE 80			
in	mm	in	mm	in	mm	PSI	lb / ft
1/2	12.70	0.840	21.336	0.147	3.734	850	0.208
3/4	19.05	1.050	26.670	0.154	3.912	690	0.280
1	25.40	1.315	33.401	0.179	4.547	630	0.411
1 1/4	31.75	1.660	42.164	0.191	4.851	520	0.569
1 1/2	38.10	1.900	48.260	0.200	5.080	470	0.690
2	50.80	2.375	6.325	0.218	5.537	400	0.957
2 1/2	63.50	2.875	73.025	0.276	7.010	420	1.460
3	76.20	3.500	88.900	0.300	7.620	370	1.950
4	101.60	4.500	114.300	0.337	8.560	320	2.844
5	127.00	5.563	141.300	0.375	9.525	290	3.953
6	152.40	6.625	168.275	0.432	10.973	280	5.433
8	203.20	8.625	219.075	0.500	12.700	250	8.251
10	254.00	10.750	273.050	0.593	15.062	230	12.243
12	304.80	12.750	323.850	0.687	17.450	230	16.831
14	355.60	14.000	355.600	0.750	19.050	220	19.960
16	406.40	16.000	406.400	0.843	21.412	220	25.550